

1P CIRCULAR ASSEMBLY P/N DESCRIPTION :

1P X FE X X XX X 0 D X X
① ② ③ ④ ⑤ ⑥ ⑦

- ① Shell:
A=Shell:PSU Grey
B=Shell:PSU Black
C=Shell:PEI Grey
D=Shell:PEI Black
E=Shell:PPSU Grey
F=Shell:PPSU Black
1=Shell:PC+ABS Grey
2=Shell:PC+ABS Black

- ② Insert
T=PPS—Unmarked
U=PEEK—Unmarked











- ③ Contact Plating
2=High Gold
A=Gold flash

- ④ Number of contacts
02=2Pin
.....
14=14Pin




- ⑤ Keying
G= 0° C= 80°
A= 40° H= 170°
B= 60° J= 205°


- ⑥ Nut Colour
0= Black 2= Red 5= Green 8= Grey
1= White 4= Yellow 6= Blue

- ⑦ Logo&Nut A mark
0= No Logo A= No Logo&With Ink mark
1= With Logo B= With Logo&With Ink mark

	2 PIN	3 PIN	4 PIN	5 PIN	6 PIN	7 PIN	8 PIN	9 PIN	10 PIN	14 PIN
										
L	5	5	5	5	3	3	3	3	3	3
øD	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.5	0.5	0.5







- NOTE:
- MATERIAL:
 - SHELL: THERMOPLASTIC,UL94V-0
 - INSERT: THERMOPLASTIC,UL94V-0
 - CENTER CONTACT : COPPER ALLOY, Au PLATING
 - NUT A : THERMOPLASTIC,UL94V-0
 - NUT B : COPPER ALLOY,Ni PLATING
 - GASKET : ELASTOMER
 - NUMBER OF CONTACT : 2 TO 14 POSITION
 - RoHS DIRECTIVE COMPLIANCE
 - PANEL HOLE
 - IP64, AFTER ASSEMBLY




THIRD ANGLE PROJECTION 		TOLERANCES UNLESS OTHERWISE SPECIFIED		 Dongguan Circon Technology Co.,Ltd.			
UNITS ☒ mm ☐ INCH		0 PLC ± 1.00 1 PLC ± 0.50 2 PLC ± 0.25 3 PLC ± 4 PLC ±		TITLE: 1P CIRCULAR CONNECTOR FIXED SOCKETS/IP64			
ANGLES 0 PLC ± 3 1 PLC ± 2							
APPROVED BY	JACK	DATE	2024-3-29		DRAWING NO.	A-M-495	REV. A0
CHECKED BY	CHARLES	DATE	2024-3-29		PART NO.	1PXFEXXXXX0DXX	
DRAWN BY	ANDY	DATE	2024-3-29		SIZE: A3	SCALE: 1:1	SHEET: 1 OF 3

REV.	REVISION DESCRIPTION	ECR/ECN NO.	DATE
------	----------------------	-------------	------


KEYING (RECEPTACLE FRONT VIEW):




THIRD ANGLE PROJECTION 		TOLERANCES UNLESS OTHERWISE SPECIFIED		 Dongguan Circon Technology Co.,Ltd.			
UNITS ☒ mm ☐ INCH		0 PLC ± 1.00 1 PLC ± 0.50 2 PLC ± 0.25 3 PLC ± 4 PLC ±		TITLE: 1P CIRCULAR CONNECTOR FIXED SOCKETS/IP64			
ANGLES 0 PLC ± 3 1 PLC ± 2							
APPROVED BY	JACK	DATE	2024-3-29	C	DRAWING NO.	A-M-495	REV.
CHECKED BY	CHARLES	DATE	2024-3-29		PART NO.	1PXFEXXXXX0DXX	A0
DRAWN BY	ANDY	DATE	2024-3-29	SIZE: A3	SCALE: 1:1	SHEET: 2 OF 3	
4		3		2		1	

REV.	REVISION DESCRIPTION	ECR/ECN NO.	DATE
------	----------------------	-------------	------


PCB LAYOUT:




2 PIN




3 PIN




4 PIN




5 PIN




6 PIN




7 PIN




8 PIN



9 PIN




10 PIN



14 PIN

THIRD ANGLE PROJECTION



UNITS ■ mm □ INCH

ANGLES 0 PLC ± 3
1 PLC ± 2

TOLERANCES UNLESS
OTHERWISE SPECIFIED

0 PLC ± 1.00
1 PLC ± 0.50
2 PLC ± 0.25
3 PLC ±
4 PLC ±

APPROVED BY

JACK

DATE

2024-3-29

CHECKED BY

CHARLES

DATE

2024-3-29

DRAWN BY

ANDY

DATE

2024-3-29



Dongguan Circon Technology Co.,Ltd.

TITLE: 1P CIRCULAR CONNECTOR
FIXED SOCKETS/IP64

C

DRAWING NO.

A-M-495

REV.

PART NO.

1PXFEXXXXX0DXX

A0

SIZE: A3

SCALE: 1:1

SHEET: 3 OF 3

REV.

REVISION DESCRIPTION

ECR/ECN NO.

DATE